

# NEW PRODUCT

**KINTRONIC LABS, INC.**

**MODEL FMC-0.2P STL\* ISOCOUPLER**

**BROADBAND PERFORMANCE AT A LOW PRICE!**

Designed to yield  
Broadband  
Isolation of an  
STL\* Dish  
Transmission Line  
Across the Base  
of a "Hot" AM  
Tower.

\* STL: Studio-Transmitter Link



FMC-0.2P Isocoupler With Inclusive Mounting Brackets and Standoff Insulators.

Note: The Tower Round Member Adaptors Are Optional

## SPECIFICATIONS

Frequency BAND:	935-985 mHz
VSWR:	<1.1:1
Insertion Loss:	<0.65 db
Power Rating:	200 Watts
RF Voltage Rating:	10KV Peak
Impedance:	50 Ohms In and Out
Capacitance:	<65 pf

## FEATURES

- Type N Female Connectors In and Out
- Can Be Post-Mounted Or Mounted Directly On Tower Leg With Optional Mounting Kit
- Comes With Complete Installation Details
- Available in Stock For Quick Delivery

P. O. Box 845  
Bristol, TN 37621  
WEB SITE: <http://www.kintronic.com>



Phone (423) 878-3141  
Fax (423) 878-4224  
EMAIL: [kti@kintronic.com](mailto:kti@kintronic.com)