

Obstruction Lighting Controller

Supports:

- **1 Dual RED / WHITE LED Beacon, Type L864/L865**
- **2 Levels of LED Obstruction Lights, Type L810**
- **Interfaces with Slave Controllers (if required)**

Features:

- **100/230 VAC, 50/60Hz**
- **Solid State Alarm Modules, Encapsulated to Protect Against Harsh Conditions and Vibration.**
- **Line Voltage Transient Protection**
- **Fused Outputs to Obstruction Light Levels.**
- **Failure Detection for:**
 - **RED LED Beacon Failure or RED Flasher Failure**
 - **Automatically Backs Up to WHITE LED Strobe at the Proper Intensity**
 - **WHITE LED Strobe Failure**
 - **Obstruction Light Failure**
 - **Power Failure**
- **Local LED Indicators for:**
 - **RED LED Beacon/Flasher Failure (Quantity 1)**
 - **WHITE LED Strobe Failure (Quantity 1)**
 - **Obstruction Light Failure (Quantity 1)**
 - **Night Mode**
 - **Power Present**
- **Night Mode System Status**
- **Individual Isolated Alarm Contacts for Remote Alarming for:**
 - **RED LED Beacon Failure (Quantity 1)**
 - **WHITE LED Strobe Failure (Quantity 1)**
 - **Obstruction Light Failure (Quantity 1)**
 - **Power Failure**
- **Test Switches Inside Controller**
- **NEMA 4 Rated Enclosure, Wall Mount**