



KINTRONIC LABS

an ISO 9001 registered company

FM Motorized Coaxial Switches



CS-FM0.5KN

Connectors: Type N
Frequency Range: DC to 862
Insertion Loss: < 0.05 dB
Input/Output Impedance: 50 ohms
Operating Voltage: 24Vdc
Control Voltage: 24Vdc
Switch-over Time: < 1 second
Return Loss: > 40 dB
Isolation: > 80 dB
Max Power: 500 W
Temp. Range: 14 – 122°F
Overall Dims: 5" W x 5" D x 6" H
Weight: 4 Lbs

CS-FM5K78EIA

Connectors: 7/8 EIA
Frequency Range: DC to 862
Insertion Loss: < 0.05 dB
Input/Output Impedance: 50 ohms
Operating Voltage: 85-264Vac; 47-63Hz
Control Voltage: 5, 12 or 24 Vdc
Switch-over Time: < 1 second
Return Loss: > 40 dB
Isolation: > 80 dB
Max Power: 5kW
Temp. Range: 14 – 122°F
Overall Dims: 6.5" W x 6.5" D x 7" H
Weight: 5.5 Lbs

CS-FM2K716DIN

Connectors: 7/16 DIN
Frequency Range: DC to 862
Insertion Loss: < 0.05 dB
Input/Output Impedance: 50 ohms
Operating Voltage: 24 Vdc
Control Voltage: 24 Vdc
Switch-over Time: < 1 second
Return Loss: > 40 dB
Isolation: > 80 dB
Max Power: 2kW
Temp. Range: 14 – 122°F
Overall Dims: 5" W x 5" D x 6" H
Weight: 4 Lbs



KINTRONIC LABS

an ISO 9001 registered company



CS-FM10K158EIA

Connectors: 1-5/8 EIA
Frequency Range: DC to 862
Insertion Loss: < 0.05 dB
Input/Output Impedance: 50 ohms
Operating Voltage: 220Vac; 50/60Hz
Control Voltage: 5, 12 or 24 Vdc
Switch-over Time: < 3.3 seconds
Return Loss: > 40 dB
Isolation: > 80 dB
Max Power: 10kW
Temp. Range: 14 – 122°F
Overall Dims: 8" W x 8" D x 12" H
Weight: 14 Lbs

CS-FM40K318EIA

Connectors: 3-1/8 EIA
Frequency Range: DC to 862
Insertion Loss: < 0.05 dB
Input/Output Impedance: 50 ohms
Operating Voltage: 220Vac; 50/60Hz
Control Voltage: 5, 12 or 24 Vdc
Switch-over Time: < 3.3 seconds
Return Loss: > 40 dB
Isolation: > 75 dB
Max Power: 40kW
Temp. Range: 14 – 122°F
Overall Dims: 11" W x 11" D x 13" H
Weight: 31 Lbs